

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 August 2003 (28.08.2003)

PCT

(10) International Publication Number
WO 03/070211 A1

(51) International Patent Classification⁷: **A61K 7/50**,
A47K 7/03

Roland [US/US]; Unilever Home & Personal Care USA,
40 Merritt Boulevard, Trumbull, CT 06611 (US).

(21) International Application Number: PCT/EP03/00794

(74) Agent: **MULDER, Cornelis, Willem, Re;** Unilever PLC,
Patent Department, Colworth House, Sharnbrook, Bedford,
Bedfordshire MK44 1LQ (GB).

(22) International Filing Date: 27 January 2003 (27.01.2003)

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:
10/079,290 19 February 2002 (19.02.2002) US

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for AE, AG, AU, BB, BZ, CA, CY, GB, GD, GH, GM, IE, IL, KE, LC, LK, LS, MN, MW, NZ, OM, SC, SD, SG, SL, SZ, TT, TZ, UG, VC, ZA, ZM, ZW only*): **UNILEVER PLC** [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicant (*for AL, AM, AT, AZ, BA, BE, BF, BG, BJ, BR, BY, CF, CG, CH, CI, CM, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, FR, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IS, IT, JP, KG, KP, KR, KZ, LR, LT, LU, LV, MA, MC, MD, MG, MK, ML, MR, MX, MZ, NE, NL, NO, PH, PL, PT, RO, RU, SE, SI, SK, SN, TD, TG, TJ, TM, TN, TR, UA, UZ, VN, YU only*): **UNILEVER NV** [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(71) Applicant (*for IN only*): **HINDUSTAN LEVER LIMITED** [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **BERGQUIST, Paul**,

(54) Title: PUCKER RESISTANT COSMETIC SACHET

(57) Abstract: An article is provided for cleansing surfaces, the article includes a curvilinear pouch formed from a plurality of walls, at least one of the walls being water permeable, and at least one of the walls being formed from at least one web of non-woven entangled fibers, the fibers being entangled in a direction perpendicular to a major longitudinal axis of the web. An effervescent cleanser composition which is an anhydrous dry solid activatable by water to generated gases is held within the pouch, and upon generation of gases the pouch walls billow outwardly. Orientation of the entangled fibers in the direction of the minor axis minimizes puckering of the article in use.

WO 03/070211 A1

- 1 -

PUCKER RESISTANT COSMETIC SACHET

The invention concerns inflatable sachets containing an effervescent dry powder activatable to release gases and
5 thereby outwardly billow the sachet.

Cleansing products have traditionally been marketed in the form of bar soaps, shower gels and mousses, the lather being generated by mechanical and aerosol dispensers. Mechanical implements have been used by consumers to assist in lather
10 formation and physical removal of dirt through scrubbing. Wash cloths have been the implement of choice throughout recent history.

New formats for cleansing hold great consumer appeal. For instance, surfactant and conditioner compositions have been
15 layered into apertured wipes such as disclosed in U.S. Patent 6,280,757 (McAtee et al.). Open-mesh sponges such as described in U.S. Patent 6,066,607 (Gordon et al.) have assisted in generating foam from shower gels thereby improving speed and quality of lathering.

20 U.S. Patent 5,980,931 (Fowler et al.) describes a substantially dry, disposable personal care article wherein a surfactant system is dried onto a water-insoluble non-woven or similar substrate. A second generation of dual layered towelette has been reported. See WO 00/42961
25 (Smith), WO 01/08542 (Cen et al.), WO 01/08640 (Smith et al.), WO 01/08641 (Lorenzi et al.), WO 01/08655 (Phipps et al.), WO 01/08656 (Lorenzi et al.), WO 01/08657 (Lorenzi et al.) and WO 01/08658 (Cawkwell et al.) all describing

- 2 -

disposable personal cleansing towelettes with lathering
surfactant on at least a two layer cloth with one layer
being a high loft substrate. Consumers are expected to
place the towelette under water to generate a surfactant
5 lather.

Another approach is described in U.S. Patent 6,063,390
(Farrell et al.) which reports a wiping article structured
as a pouch containing an effervescent cleanser composition.
At least one of the pouch walls are water permeable. When
10 wetted with water, the composition components of an acid
material and an alkaline material effervesce to generate
carbon dioxide, as well as exuding copious amounts of lather
from a surfactant component. A plumped "pillow" arises from
the effervescent action.

15 EP 0 836 842 B1 (Moore et al.) discloses oval shaped
disposable non-woven cleaning articles. These are formed of
hydro-entangled fibers wherein entanglement is oriented in a
direction parallel to the major axis of the oval.

Elongate shaped pouches are particularly suitable for
20 gripping; they tend to more ergonomically fit within the
hand. For the present invention, an effervescent sachet
system was sought which would be easily grippable.

A problem encountered with sachets formed from non-woven
materials is their tendency to pucker. When the dry
25 effervescent composition is activated with water, the
resultant evolution of gases inflates the sachet into a
bulging pillow arrangement. Deformation of the sachet walls
results in a substantial pucker of the pillow configuration.

- 3 -

Both for aesthetic and ergonomic reasons, the pucker is undesirable.

Accordingly, it is an object of the present invention to provide a cosmetic article with an activatable effervescent
5 cleansing system which upon inflation by effervescent gases causes the article to inflate but avoids deformation and puckering of the article.

It is to be noted that the subsequently described invention is broader than the objects or technical problems it is
10 directed to solve.

According to a first aspect an article is provide for cleansing surfaces, the article including:

- a curvilinear pouch formed from a plurality of walls, at least one of the walls being water
15 permeable, and at least one of the walls being formed from at least one web of non-woven entangled fibers, the fibers being entangled in a direction perpendicular to a major longitudinal axis of the web; and

20 - an effervescent cleanser composition which is an anhydrous dry solid activable by water to generate gases, the composition being held within the pouch, and upon generation of gases the pouch walls billowing outwardly.

25 Further objects, features and advantages of the present invention will become more readily apparent from consideration of the drawings, in which:

- 4 -

- Fig. 1 is a plan perspective view of a first embodiment in the form of an oval sachet;

- Fig. 2 is a cross-section along line 2-2 of the first embodiment shown in Fig. 1;

5 - Fig. 3 is a front elevational view of a second embodiment of a sachet according to the present invention;

10 - Fig. 4 is a front elevational view of a third embodiment of a sachet according to the present invention; and

 - Fig. 5 is a front elevational view of a fourth embodiment of a sachet according to the present invention.

Now it has been found that proper orientation of fibers in a
15 non-woven web forming a wall of the pouch can avoid the problem of puckering. Upon release of gases through water activation of the effervescent composition, the walls of the pouch billow outwardly. Directed orientation of the entangled fibers forming a web which is at least part of the
20 pouch wall allows the system to stretch, thereby avoiding deformation and any substantial puckering.

Fig. 1 illustrates a first embodiment wherein the pouch is oval shaped.

The pouch 2 has walls formed by a first spun lace web 4 and
25 a second meltblown composite web 6, the latter being bonded to a high loft sheet 8. The webs forming webs 4 and 6 are non-woven entangled fiber matrices. Fig. 2 best illustrates

- 5 -

by cross-section the several webs constituting the walls. Chamber 10 formed between the first and second webs 4, 6 serves to confine a powdered effervescent composition 12. Webs 4 and 6 are ultrasonically sealed along a
5 circumferential track 14 to insure no loss of the powdered composition.

Pouch 2 is defined by a major axis M oriented in a longitudinal direction and a minor axis N oriented in a lateral direction, the major axis being longer than the
10 minor one.

Fig. 3 is a second embodiment of the invention. It illustrates a crescent-shaped sachet 16. Major and minor axes, (M' and N'), are outlined on the Figure.

Fig. 4 illustrates a third embodiment according to the
15 present invention. Sachet 22 along one edge has a sinusoidal shape 24 and along an opposite edge a straight configuration 26. Major and minor axes are identified as M'' and N''.

Fig. 3 and 4 provide particularly useful curvilinear edges
20 because of their more grippable and less slip-prone configuration relative to that of an oval. Yet the problem of puckering is particularly aggravated in configurations having concave edges such as identified by 18 and 28.

Fig. 5 illustrates a fourth embodiment. Sachet 32 at the
25 ends of the major axis M''' has a straight edge 36 and at opposite ends a rounded edge 34. Minor axis N''' traverses the major axis.

- 6 -

Copious foam is generated when pouch 2 is wetted with water, much in the same manner as a toilet bar is lathered.

Physically, the pouch is constructed in an oval shape with a size fittable within a human hand thereby simulating a
5 toilet bar.

The term "major axis" refers to the longitudinal direction or length and is defined as the direction parallel to the longitudinal center line of the sachet. Normally the major axis coincides with the material direction (MD) along which
10 the web is produced. In other words, as fibers are laid down they are conveyed as a web away from the depositing source in a MD movement. The term "minor axis" refers to the lateral direction or width, and is defined as the direction perpendicular to the longitudinal center line of
15 the sachet. Normally the minor axis coincides with the cross direction (CD) arranged orthogonal to the MD along which the web is produced.

Tensile Strength of nonwovens is ordinarily strongest in the machine direction. Entanglement oriented webs of the
20 present invention seek to improve strength in the CD relative to the MD length. However, the resultant oriented webs will not necessarily exhibit higher tensile strength in the CD than MD length; but tensile strength differences will have been narrowed. For instance, a spun lace fabric may be
25 formed from fiber deposition that is CD to MD in a tensile strength ratio of circa 1:4. Subsequent hydroentanglement orientation enhances the ratio to circa 1:2. Preferably orientation of entangled fibers will increase tensile strength by at least 20%, more preferably by at least 50%,
30 and optimally by at least 100% in CD versus MD value.

- 7 -

Typical dimensions for the major axis may range from about 20 mm to about 300 mm, preferably from about 30 to about 100 mm. Dimensions of the minor axis may range from about 30 to about 85 mm, preferably from about 20 to about 50 mm.

- 5 Orientation of the fibers of the present invention is not limited to any particularly technique. In fact, any technique known in the art can be employed to gain the desired orientation effect.

The pouch comprises at least one web of entangled fibers.

- 10 The entangled fibers are entangled in a direction perpendicular to the major axis of the pouch. The preferred method of manufacturing entangled fibers utilizes a process known as hydroentangling. A hydroentangled web that is strong and durable is produced by traversing material fibers
15 with high energy jet streams of water in order to interlock the fibers. Other high pressure fluids can be used in place of water.

- Although hydroentangling is preferred as the method of producing the entangled web, other methods can alternatively
20 be employed. Needlepunching is an example of a method which can be employed. In this method, barbed needles are punched through the web, hooking tufts of fibers across it and thereby bonding it in the needlepunched areas. Another method which can be utilized is thermal bonding, in which
25 the fibers are of thermoplastic material, or have an outer layer of thermoplastic material, and are bonded together in discrete spots by heat. A web produced in this way is unlikely to be as soft as one produced by hydroentangling,

- 8 -

or needlepunching, and it may have a substantial proportion of completely loose fibers.

Yet another method involves wet-laying a mixture of fibers and chemical binder, somewhat in the manner employed, for example, in paper making. Yet a further method is carding, in which staple fibers are opened, cleaned, aligned and formed into a continuous unbonded web. While hydroentangling, and chemically, thermally, mechanically bonded materials and carded materials are representative of the technologies which can be incorporated in the present invention, these do not exhaust all the possibilities. Other technologies such as embossing, creping and aperturing can be incorporated into the manufacture of the pouch.

Web 6 may be a single meltblown web, but preferably it is a combination of several layers forming a composite web. One embodiment utilizes the three layers of spunbond/meltblown/spunbond (SMS) and another utilizes four layers representing spunbond/meltblown/meltblown/spunbond (SMMS) construction. In these systems the meltblown fibers are very compact and act as a barrier against loss of powder. The spunbond layers are provided for strength and softness.

The meltblown web can be any meltblown web made from a thermoplastic polymer having a melting point greater than about 50°C. A preferred polymer is polypropylene, which is the most commonly used polymer for making meltblown webs. Other suitable polymers include poly(butylene terephthalate), polycaprolactam, poly(ethylene terephthalate) and polyethylene.

- 9 -

The process for making meltblown webs is well known in the art and is used extensively for manufacturing a wide variety of commercial nonwoven products. Representative examples of the meltblowing process are described in U.S. Pat. No. 5 3,978,185 to Buntin et al. dated August 31, 1976; U.S. Patent No. 4,298,649 to Meitner dated November 3, 1981; and U.S. Patent No. 4,100,324 to Anderson et al. dated July 11, 1978, all herein incorporated by reference. It will be appreciated, however, that other meltblowing processes will 10 produce webs suitable for purposes of this invention. The meltblown web can be combined or laminated to other supporting webs, such as spunbonded webs, in order to impart strength or other attributes to the product.

The basis weight for a single sheet of the meltblown base 15 webs of this invention can range from about 20 to about 300 grams per square meter. Preferably the basis weight will be from about 80 to about 250, and most preferably from about 100 to about 200 grams per square meter.

Spunbonding entails extruding a multiplicity of continuous 20 thermoplastic polymer strands through a multiplicity of die orifices in a downward direction onto a moving surface where the extruded strands are collected in randomly distributed fashion. The randomly deposited strands are then bonded together in a heated nip to provide sufficient integrity to 25 the resulting nonwoven web of continuous fibers. Spunbonded webs are characterized by a high strength/weight ratio, isotropic strength, high porosity, and good abrasion resistance.

- 10 -

Meltblowing differs from spunbonding in that the extruded polymer strands are broken up and dispersed into individual fibers by a forced air stream before being deposited onto the collecting surface. In addition, the fibers are
5 substantially cooled by the air so that they do not significantly crystallize and/or bond together. Bonding of the web to retain integrity and strength occurs as a separate downstream operation.

A most preferred material for the second web 6 is a non-woven meltblown/spunbond substrate available from the
10 Polyprop Corporation.

The first web 4 preferably is either a spun lace or a carded/chemically bonded non-woven water-insoluble material. Particularly preferred is a cloth NC008 (Image Spun Lace)
15 available from the PGI Corporation.

When present, a high loft sheet may be utilized as the water-permeable wall. As used herein, "high loft" means that the sheet has a density of from about 0.00005 g/cm^3 to about 0.1 g/cm^3 , preferably from about 0.001 g/cm^3 to about
20 0.09 g/cm^3 and a thickness of from about 0.1 cm to about 5 cm.

As used herein, "nonwoven" means that the layer does not comprise fibers which are woven into a fabric. The term "curvilinear" means that at least one edge defining the
25 pouch is a curved surface. Preferably the pouch exhibits no squared corners.

- 11 -

For purposes of this invention, the most preferred high loft material is a needle punched composite sold by Union Wadding Corporation.

Sachets of the present invention may be produced by
5 depositing a charge of effervescent powder through a funnel nozzle onto an oriented nonwoven web as it moves in a horizontal manner. Downstream a similarly oriented hydro-entangled web is unfurled from a roll and travels in a direction above and parallel to that of the first web. The
10 parallel webs and deposited effervescent powder then pass underneath a stamping station which heat seals in an oval pattern the first and second webs together with the effervescent powder charge between the web walls. Subsequently, a cutter die punches out the heat sealed oval
15 article.

One or more of the articles may then be packaged within a moisture impermeable outer package such as a laminated foil bag to prevent activation of the effervescent system during storage.

20 Ultrasonic welding may be employed as an alternative to heat-sealing of the first and second substrates together. Thread stitching, glue application or other closure mechanisms may also be utilized.

A first component of compositions 12 within the pouch is
25 that of an acidic material. Suitable for this purpose are any acids, and preferably those present in dry solid form. Especially appropriate are C₂-C₂₀ organic mono- and poly-carboxylic acids and especially alpha- and beta-

- 12 -

hydroxycarboxylic acids; C₂-C₂₀ organophosphorus acids such as phytic acid; C₂-C₂₀ organosulfur acids such as toluene sulfonic acid; and peroxides such as hydrogen peroxide. Typical hydroxycarboxylic acids include adipic, glutaric, 5 succinic, tartaric, malic, maleic, lactic, salicylic and citric acids as well as acid forming lactones such as gluconolactone and glucarolactone. Most preferred is citric acid. Also suitable as acid material may be encapsulated acids. Typical encapsulating material may include water 10 soluble synthetic or natural polymers such as polyacrylates (e.g. encapsulating polyacrylic acid), cellulosic gums, polyurethane and polyoxyalkylene polymers.

By the term "acid" is meant any substance which when dissolved in deionized water at 1% concentration will have a 15 pH of less than 7, preferably less than 6.5, optimally less than 5. These acids preferably at 25°C are in solid form, i.e. having melting points no less than 25°C. Concentrations of the acid should range from about 0.5 to about 80%, preferably from about 10 to about 65%, optimally from about 20 20 to about 45% by weight of the total composition.

A second component of compositions within the pouch is that of an alkaline material. The alkaline material is a substance which can generate a gas such as carbon dioxide, nitrogen or oxygen, i.e. effervesce, when contacted with 25 water and the acidic material. Suitable alkaline materials include anhydrous salts of carbonates and bicarbonates, alkaline peroxides (e.g. sodium perborate and sodium percarbonate) and azides (e.g. sodium azide). Preferably the alkaline material is sodium or potassium bicarbonate.

- 13 -

Amounts of the alkaline material may range from about 1 to about 80%, preferably from about 5 to about 49%, more preferably from about 15 to about 40%, optimally from about 20 to about 35% by weight of the total composition.

- 5 By the term "anhydrous" is meant the presence of no more than about 15%, preferably no more than about 5% and optimally no more than 1% water by weight of the total composition. Water of hydration is not considered to be water for purposes of the anhydrous definition. However, it
10 is preferred to minimize, preferably to eliminate any water of hydration.

Advantageously the combined amount of acidic and alkaline materials will be at least about 1.5%, preferably from about 40 to about 95%, optimally from about 60 to about 80% by
15 weight of the total composition.

An optimal further component of compositions according to the present invention is that of a surfactant, preferably a dry surfactant solid at 20°C. Most suitable for the present invention is sodium cocoyl isethionate. Other useful
20 surfactants include sodium methyl cocoyl taurate, sodium lauroyl sarcosinate and sodium lauryl sulfate. Surfactants may be of the anionic, cationic, nonionic, amphoteric, zwitterionic varieties and combinations thereof. Amounts of the surfactant may range from about 0.1 to about 30%,
25 preferably from about 1 to about 30%, optimally from about 8 to about 20% by weight of the total composition.

A variety of skin benefit agents may be included to improve afterfeel properties. Advantageously these substances will

- 14 -

be available as anhydrous dry powders. Alternatively these substances may be liquids deposited upon or into a powdered substrate (e.g. calcium silicate or zeolite) to achieve a resultant dry flowing powder. Within the skin benefit agent scope are several categories of materials. These include emollients, antiaging actives, antibacterials and fungicides, skin lighteners, sunscreens and combinations thereof. Amounts of the skin benefit agents may range from about 0.001 to about 40%, preferably from about 0.1 to about 20%, more preferably from about 0.5 to about 10%, optimally between about 1 and about 5% by weight of the total composition.

Emollients may be in the form of natural or synthetic esters, silicone oils, hydrocarbons, starches, fatty acids and mixtures thereof. Typically the emollient may range in concentration from about 0.1 to about 35% by weight of the total composition.

Silicone oils may be divided into the volatile and nonvolatile variety. The term "volatile" as used herein refers to those materials which have a measurable vapor pressure at ambient temperature (25°C). Volatile silicone oils are preferably chosen from cyclic or linear polydimethylsiloxanes containing from 3 to 9, preferably from 4 to 5, silicon atoms.

Linear volatile silicone materials generally have viscosities less than about 5 centistokes at 25°C while cyclic materials typically have viscosities of less than about 10 centistokes.

- 15 -

- Nonvolatile silicone oils useful as an emollient material include polyalkyl siloxanes, polyalkylaryl siloxanes and polyether siloxane copolymers. The essentially non-volatile polyalkyl siloxanes useful herein include, for example,
- 5 polydimethyl siloxanes with viscosities of from about 5 to about 100,000 centistokes at 25 °C. Among the preferred non-volatile emollients useful in the present compositions are the polydimethyl siloxanes having viscosities from about 10 to about 400 centistokes at 25°C.
- 10 Among the ester emollients are:
- (1) Alkenyl or alkyl esters of fatty acids having 10 to 22 carbon atoms. Examples thereof include isoarachidyl neopentanoate, isononyl isononanoate, oleyl myristate, oleyl stearate, and oleyl oleate.
 - 15 (2) Ether-esters such as fatty acid esters of ethoxylated fatty alcohols.
 - (3) Polyhydric alcohol esters. Ethylene glycol mono and di-fatty acid ester, diethylene glycol mono- and di-fatty acid esters, polyethylene glycol (200-8000) mono- and di-fatty acid esters,
 - 20 polypropylene glycol 2000 monooleate, polypropylene glycol 2000 monostearate, ethoxylated propylene glycol monostearate, glyceryl mono- and di-fatty acid esters,
 - 25 polyglycerol poly-fatty esters, ethoxylated glyceryl monostearate, 1,3-butylene glycol monostearate, 1,3-butylene glycol distearate, polyoxyethylene polyol fatty acid ester, sorbitan

- 16 -

fatty acid esters, and polyoxyethylene sorbitan fatty acid esters are satisfactory polyhydric alcohol esters.

5 (4) Wax esters such as beeswax, spermaceti, myristyl myristate, stearyl stearate and arachidyl behenate.

(5) Sterols esters, of which cholesterol fatty acid esters are examples thereof.

10 (6) Triglycerides such as sunflower seed oil, maleated sunflower seed oil, polycottonseedate, borage seed oil and safflower oil.

Hydrocarbons suitable as emollients include petrolatum, mineral oil, isoparaffins and hydrocarbon waxes such as polyethylene.

15 Starches are also suitable emollients. Typical of this class is tapioca and arabinogalactan.

Fatty acids may also be suitable as emollients. The fatty acids normally have from 10 to 30 carbon atoms.

20 Illustrative of this category are pelargonic, lauric, myristic, palmitic, stearic, isostearic, hydroxystearic, oleic, linoleic, ricinoleic, arachidic, behenic and erucic acids.

Antiaging actives are also useful as skin benefit agents. Included within this category are vitamins, retinoids and
25 combinations thereof. Amounts of these materials may range from about 0.001 to about 20% by weight of the total composition. Suitable vitamins include ascorbic acid,

- 17 -

Vitamin B₆, Vitamin B₁₂, tocopherol as well as salts and C₁-C₂₀ esters thereof. Suitable retinoids include retinoic acid as well as its C₁-C₂₂ esters and salts, retinol and C₁-C₂₂ fatty esters of retinol including retinyl linoleate.

5 Another class of antiaging actives are the alpha- and beta-hydroxycarboxylic acids and salts thereof. Representative of this group are glycolic acid, lactic acid, malic acid, hydroxyoctanoic acid, salicylic acid and mixtures of these as well as their salts. Suitable salts are the alkalimetal,
10 ammonium and C₁-C₁₀ alkanol ammonium salts.

Antibacterials and fungicidals may also be included as skin benefit agents. Representative of these categories are triclosan, tricloban, hexetidene, chlorhexadene, gluconates, zinc salts (e.g. zinc citrate and zinc phenolsulfonate) and
15 combinations thereof.

Skin lighteners may also be included under the skin benefit agents. Typical of this category are niacinamide, kojic acid, arbutin, vanillin, ferulic acid and esters thereof, resorcinol, hydroquinone, placental extract and combinations
20 thereof.

Sunscreens may also be included as skin benefit agents. Particularly preferred are such materials as ethylhexyl p-methoxycinnamate, available as Parsol® MCX, avobenzene available as Parsol® 1789 and benzophenone-3, also known as
25 Oxybenzone. Inorganic sunscreen actives may be employed such as microfine titanium dioxide, polyethylene and various

- 18 -

other polymers. Amounts of the sunscreen agents may generally range from 0.1 to 30%, preferably from 2 to 20%, optimally from 4 to 10% by weight.

Adjunct functional agents may also be incorporated into compositions of the present invention. These include electrolytes, thickeners and mixtures thereof. Amounts of these substances may range from about 0.1 to about 20%, preferably from about 0.3 to about 10%, optimally between about 0.5 and about 5% by weight of the total composition.

Electrolytes may be selected from alkali, alkaline earth or ammonium salts of phosphates, silicates, halides, sulphates and mixtures thereof. Typical phosphates are potassium polymetaphosphate, sodium tripolyphosphate, sodium tetrapyrophosphate, sodium or potassium pyrophosphate and sodium hexametaphosphate. Most preferred is potassium polymetaphosphate available as Lipothix 100B® which is a 70:30 mixture of potassium polymetaphosphate and sodium bicarbonate, available from Lipo Chemicals, Inc., Paterson, New Jersey. Preferred sulphates are the magnesium sulphates.

Thickeners which may improve afterfeel properties on skin include inorganic or organic substances. A particularly preferred inorganic thickener is sodium magnesium silicate commercially available as Optigel SH®. Organic thickeners include alginic acid as well as sodium and calcium alginates, sodium carboxymethyl cellulose, hydroxypropyl methylcellulose, hydroxypropyl cellulose, hydroxyethyl cellulose and combinations thereof. Most preferred is

- 19 -

alginic acid commercially available as Kelacid® from Sud-Chemie Rheologicals, Louisville, Kentucky. Alginic acid is highly effective at removing the slimy feel associated with deposits of alkaline material which are not fully rinsed
5 away from the skin. Amounts of the thickener may range from about 0.1 to about 20%.

Polysaccharides useful in this invention are dry solid anhydrous substances such as sorbitol, sugars, (such as trehalose), starches, modified starches (e.g. aluminum
10 octenyl succinate) and mixtures thereof. Most preferred is sorbitol.

Deposition aids may also be incorporated in compositions of the present invention. These assist in depositing skin benefit agents onto the skin surface. Particularly
15 effective are cationic monomers and polymers for this purpose. Illustrative are the following:
Lauryltrimethylammonium chloride; Stearyltri(2-hydroxyethyl)ammonium chloride; Lauryldimethylbenzylammonium chloride; Cetyldimethylbenzylammonium chloride;
20 Cetylpyridinium chloride; Polydiallyldimethylammonium chloride; Diallyldimethylammonium salt copolymerized with acrylamide; Guar hydroxypropyltrimonium chloride; Cationic hydroxyethylcellulosics; Cationic hydroxyethylcellulosics; Cetyltrimethylammonium chloride; Decyldimethyloctylammonium
25 chloride; and Myristyltrimethylammonium chloride.

Most preferred for purposes of this invention are cationic guar gums such as Jaguar C13S® which is guar hydroxypropyltrimonium chloride and Polyquaternium 7 commercially available as Merquat 2200. Amounts of the

- 20 -

deposition aid may range from about 0.01 to about 1%, preferably from about 0.05 to about 0.5%, optimally from about 0.1 to about 0.3% by weight.

Advantageously an emotive agent such as a fragrance and/or botanical extract are included with the effervescent cleansing composition. Fragrances and botanicals are often liquids. For this reason it may be necessary to uniformly distribute and allow absorption of liquid components into the solid powder. One method of best achieving this is to spray these liquids onto the solids. Amounts of the fragrance and/or botanicals combined may be at levels from about 0.1 to about 3%, preferably from 0.5 to 2%, optimally from 0.8 to 1.5% by weight of the total composition.

The term "fragrance" is defined as a mixture of odoriferous components, optionally mixed with a suitable solvent diluent or carrier, which is employed to impart a desired odor. Particular preferred odoriferous components are cyclic and acyclic terpenes and terpenoids. These materials are based upon isoprene repeating units. Examples include alpha and beta pinene, myrcene, geranyl alcohol and acetate, camphene, dl-limonene, alpha and beta phellandrene, tricyclene, terpinolene, allocimmane, geraniol, nerol, linanool, dihydrolinanool, citral, ionone, methyl ionone, citronellol, citronellal, alpha terpineol, beta terpineol, alpha fenchol, borneol, isoborneol, camphor, terpinen-1-ol, terpin-4-ol, dihydroterpineol, methyl chavicol, anethole, 1,4 and 1,8 cineole, geranyl nitrile, isobornyl acetate, linalyl acetate, caryophyllene, alpha cedrene, guaiaol, patchouli alcohol, alpha and beta santalol and mixtures thereof.

- 21 -

Botanicals of particular use in the present invention include yarrow, chamomile, jasmine, lavender, horse chestnut, sage, thyme, yucca, coltsfoot and mixtures thereof.

5 Preservatives can desirably be incorporated into the cosmetic compositions of this invention to protect against the growth of potentially harmful microorganisms. Suitable traditional preservatives for compositions of this invention are alkyl esters of para-hydroxybenzoic acids. Other
10 preservatives which have more recently come into use include hydantoin derivatives, propionate salts, and a variety of quaternary ammonium compounds. Cosmetic chemists are familiar with appropriate preservatives and routinely choose them to satisfy the preservative challenge test and to
15 provide product stability. Particularly preferred preservatives are phenoxyethanol, methyl paraben, propyl paraben, imidazolidinyl urea, sodium dehydroacetate and benzyl alcohol. Preservatives are preferably employed in amounts ranging from 0.01% to 2% by weight of the
20 composition.

Colorants may also be included in compositions of the present invention. These substances may range from about 0.05 to about 5%, preferably between 0.1 and 3% by weight.

It is important that the webs are not readily torn open
25 through consumer rubbing of the article. Unlike laundry sachet articles, pouches of the present invention should not rupture to allow dispersion of their granular contents into wash water. Rather it is intended for all composition

- 22 -

components to exit by dissolution through the permeable walls of the pouch.

Skin surfaces against which articles of the present invention are useful include face, body, scalp, axilla and
5 even legs/feet. When the article is a foot cleanser, it would be advantageous for the pouch on one of its sides to be coarse while the second of the substrates may be soft and gentle.

Except in the operating and comparative examples, or where
10 otherwise explicitly indicated, all numbers in this description indicating amounts of material are to be understood as modified by the word "about".

The term "comprising" is meant not to be limiting to any subsequently stated elements but rather to encompass non-
15 specified elements of major or minor functional importance. In other words the listed steps, elements or options need not be exhaustive.

The following examples will more fully illustrate embodiments of this invention. All parts, percentages and
20 proportions referred to herein and in the appended claims are by weight unless otherwise indicated.

EXAMPLE 1

An effervescent cleansing composition was prepared according
25 to the formulation reported in Table I. Phase A was dry blended in a high speed shearing mixer. Fragrance was then sprayed onto the resultant powder as a Phase B. Three grams

- 23 -

of the resultant powder are then placed into a pocket of a 5cm by 8cm oval pouch. Walls of the pouch are formed by heat sealing the circumferences of a non-woven spun lace web to a non-woven SMMS composite web. The spun lace web is a material whose fibers have been oriented in a direction perpendicular of the major axis of the pouch (i.e. in the cross direction).

TABLE I

INGREDIENT	WEIGHT %
PHASE A	
Sodium Bicarbonate	34.5
Citric Acid (Anhydrous)	40.4
Sodium Cocoyl Isethionate (Powder)	11.6
Sodium Sesquicarbonate	5.0
Lipothix 100B® (Potassium Polymetaphosphate/Bicarbonate 70:30)	0.5
Optigel SH® (Sodium Magnesium Silicate)	1.0
Kelacid® (Alginic Acid)	1.0
Sorbitol	5.0
PHASE B	
Fragrance	1.0

10 EXAMPLE 2

Another effervescent cleansing composition was prepared according to the formulation reported in Table II. The composition is then sealed into a pouch as described in Example 1.

- 24 -

TABLE II

INGREDIENT	WEIGHT %
PHASE A	
Sodium Bicarbonate	32.3
Citric Acid (Anhydrous)	41.1
Sodium Cocoyl Isethionate (Powder)	11.6
Sodium Sesquicarbonate	5.0
Lipothix 100B® (Potassium Polymetaphosphate/Bicarbonate 70:30)	0.5
Optigel SH® (Sodium Magnesium Silicate)	1.0
Kelacid® (Alginic Acid)	1.0
Sorbitol	5.0
Laracare A200® (Arabinogalactan)	1.0
Ascorbic Acid	0.5
PHASE B	
Fragrance	1.0

EXAMPLE 3

A face cleansing effervescent composition was prepared according to the formulation reported in Table III. The composition is then sealed into a pouch as described in Example 1.

- 25 -

TABLE III

INGREDIENT	WEIGHT %
PHASE A	
Sodium Bicarbonate	33.6
Citric Acid (Anhydrous)	39.0
Sodium Cocyl Isethionate (Powder)	3.0
Sodium Methyl Cocoyl Taurate	6.0
Sodium Lauryl Sulfate	2.5
Sodium Sesquicarbonate	5.0
Lipothix 100B® (Potassium Polymetaphosphate/Bicarbonate 70:30)	0.5
Optigel SH® (Sodium Magnesium Silicate)	2.0
Tapioca	5.5
Methyl Gluceth 20-Benzoate	2.0
Guar Hydroxypropyl Trimonium Chloride	0.25
PHASE B	
Fragrance	0.65

EXAMPLE 4

A still further effervescent cleansing composition according to the present invention may be prepared according to the formulation reported under Table IV. The dry mixed ingredients at a weight level of 3.5 grams per sample are placed into a moon-shaped pouch as shown in Fig. 3 with lengths along major and minor (width) axis of 9cm and 5.5cm. The powdered sample is placed between a layer of spunlace web and an SMS layer to which a high loft sheet is sealed. The webs of spunlace and SMS are arranged to have their fibers oriented cross to the major axis direction. All sides of the pouch are welded by ultrasonic heat to ensure against powder escaping.

- 26 -

TABLE IV

INGREDIENT	WEIGHT %
Anhydrous Citric Acid	24.00
Sodium Bicarbonate	24.00
Sodium Lauryl Sulfoacetate	3.75
Sodium Cocoyl isethionate	3.75
Polyquaternium 7	0.50
Sodium C14-C16 Olefin Sulfonate	3.75
Guar hydroxypropyltrimonium Chloride	0.40
Ascorbyl Palmitate	0.01
Isocetyl Behenate	5.00
Sodium Stearoyl Lactylate	3.00
Disodium Dimethicone Copolyol Sulfosuccinate	1.00
Vitamin A Palmitate	0.01
Sodium Lauroyl Lactylate	5.00
PEG 8000	5.00
Vitamin E	0.40
Calcium Silicate	9.00
Maltodextrin	11.13
Fragrance	0.30

- 27 -

CLAIMS

1. An article for cleansing surfaces, the article comprising:
 - 5 - a curvilinear pouch formed from a plurality of walls, at least one of the walls being water permeable, and at least one of the walls being formed from at least one web of non-woven entangled fibers, the fibers being entangled in a direction
10 perpendicular to a major longitudinal axis of the web; and
 - an effervescent cleanser composition which is an anhydrous dry solid activable by water to generate gases, the composition being held within the pouch,
15 and upon generation of gases the pouch walls billowing outwardly.
2. The article according to claim 1 wherein the entangled
20 fibers are hydroentangled.
3. The article according to claim 1 or claim 2 wherein the
 at least one web has a cross and machine direction, and
 tensile strengths of the web in the cross and machine
 directions respectively being increased by at least 20%
25 through orientation.
4. The article according to any of the preceding claims
 wherein the at least one web is a nonwoven sheet
 selected from meltblown, spunbond and spunlace
30 construction.

- 28 -

5. The article according to any of the preceding claims wherein the composition comprises from 0.5 to 80% by weight of an acid and from 1 to 80% by weight of an alkaline material.
- 5
6. The article according to any of the preceding claims wherein the pouch is oval in shape.
7. The article according to any of the preceding claims wherein the pouch is neither square nor rectangular in shape.
- 10
8. A method for cleansing body surfaces, the method comprising:
- 15 (i) preparing an article comprising:
- a curvilinear pouch formed from a plurality of walls, at least one of the walls being water permeable, and at least one of the walls being formed from at least one web of non-woven entangled fibers, the fibers being entangled in a direction perpendicular to a major longitudinal axis of the web; and
 - an effervescent cleanser composition which is an anhydrous dry solid activable by water to generate gases, the composition held within the pouch, and upon generation of gases the pouch walls billowing outwardly;
- 20
- (ii) wetting the article to generate an effervescent cleansing foam; and
- 25
- (iii) applying the wetted article with generated effervescent cleansing foam onto parts of a user's
- 30

- 29 -

body surfaces and cleansing therewith those
surfaces.

1/2

Fig.1.




Fig.2.




Fig.3.




Fig.4.





Fig.5.



INTERNATIONAL SEARCH REPORT

Inter Application No
PC, L, 03/00794

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61K7/50 A47K7/03

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61K A47K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 00 07561 A (UNILEVER PLC ; LEVER HINDUSTAN LTD (IN); UNILEVER NV (NL)) 17 February 2000 (2000-02-17) claims 1-10; example 1 ---	1-8
A	US 6 063 390 A (FARRELL LINDA ET AL) 16 May 2000 (2000-05-16) cited in the application claims 1-10 ---	1-8
A	EP 0 836 842 A (PROCTER & GAMBLE) 22 April 1998 (1998-04-22) cited in the application claims 1-8 --- -/--	1-8

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* & * document member of the same patent family

Date of the actual completion of the international search

29 July 2003

Date of mailing of the international search report

06/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Lindner, A

INTERNATIONAL SEARCH REPORT

Interr Application No
PCT/CI 03/00794

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 136 768 A (DESENNA RICHARD A ET AL) 24 October 2000 (2000-10-24) column 1, line 49 -column 2, line 26; claims 17,18 -----	1-8
A	WO 01 56542 A (UNILEVER PLC ;LEVER HINDUSTAN LTD (IN); UNILEVER NV (NL)) 9 August 2001 (2001-08-09) page 19, line 1 -page 20, line 16 -----	1-8

INTERNATIONAL SEARCH REPORT

Intern: Application No
PCT/EP 03/00794

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0007561	A	17-02-2000	US 6063390 A	16-05-2000
			AT 224700 T	15-10-2002
			AU 738364 B2	13-09-2001
			AU 4911299 A	28-02-2000
			BR 9912769 A	08-05-2001
			CA 2337716 A1	17-02-2000
			CN 1311664 T	05-09-2001
			CZ 20010489 A3	15-08-2001
			DE 69903175 D1	31-10-2002
			DE 69903175 T2	22-05-2003
			WO 0007561 A1	17-02-2000
			EP 1230915 A2	14-08-2002
			EP 1102577 A1	30-05-2001
			ES 2184476 T3	01-04-2003
			HU 0103200 A2	28-02-2002
			JP 2002522369 T	23-07-2002
			PL 345891 A1	14-01-2002
			US 6217854 B1	17-04-2001
			US 2001026792 A1	04-10-2001
			US 2002039558 A1	04-04-2002
US 6063390	A	16-05-2000	AT 224700 T	15-10-2002
			AU 738364 B2	13-09-2001
			AU 4911299 A	28-02-2000
			BR 9912769 A	08-05-2001
			CA 2337716 A1	17-02-2000
			CN 1311664 T	05-09-2001
			CZ 20010489 A3	15-08-2001
			DE 69903175 D1	31-10-2002
			DE 69903175 T2	22-05-2003
			WO 0007561 A1	17-02-2000
			EP 1230915 A2	14-08-2002
			EP 1102577 A1	30-05-2001
			ES 2184476 T3	01-04-2003
			HU 0103200 A2	28-02-2002
			JP 2002522369 T	23-07-2002
			PL 345891 A1	14-01-2002
			US 6217854 B1	17-04-2001
			US 2001026792 A1	04-10-2001
			US 2002039558 A1	04-04-2002
EP 0836842	A	22-04-1998	EP 0836842 A2	22-04-1998
			AT 200215 T	15-04-2001
			AU 4488497 A	11-05-1998
			BR 9712356 A	31-08-1999
			CN 1233993 A	03-11-1999
			DE 69612382 D1	10-05-2001
			DE 69612382 T2	20-09-2001
			ES 2155560 T3	16-05-2001
			JP 2000503577 T	28-03-2000
			KR 2000049113 A	25-07-2000
			WO 9816349 A1	23-04-1998
US 6136768	A	24-10-2000	AU 2406800 A	24-07-2000
			EP 1141214 A1	10-10-2001
			WO 0040688 A1	13-07-2000
WO 0156542	A	09-08-2001	AU 3727901 A	14-08-2001

INTERNATIONAL SEARCH REPORT

Intern. Application No
PCT/EP 03/00794

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0156542 A		WO 0156542 A1	09-08-2001
		US 6451331 B1	17-09-2002
